



## Designated as High Priority Openings

### 1. OPENINGS IN SMOKE PARTITIONS

- Non-Hose Stream Tested
- UL 10B 20 minute no hose
- ASTM E136
- ASTM E84



- SD60® Smoke Curtain® (Full Drop / Half Drop to Floor)
- SD60® Deployable Draft Curtain (18" Drop up to 24" drop)
- SD60® Fixed Fabric Draft Curtain

### 2. ELEVATOR HOISTWAY SMOKE CONTAINMENT

- ICC AC 77, CCRR 0418, ICC 3322



- SD60GS® Side Guide Seal Elevator Smoke Containment®

### 2. ELEVATOR HOISTWAY SMOKE CONTAINMENT

- ICC AC 77, ESR 4888



- ESC Magnetic Seal Elevator Smoke Containment

### 3. OPENINGS IN SMOKE BARRIER WALLS AND FIRE PARTITION WALLS

- UL 10D
- UL 1784
- Not Hose Stream Tested



- SD60GS® 1Hr Fire Protective Smoke Curtain with Egress
- SD240GS® 2 Hr Fire Protective Smoke Curtain
- SD240GS® 2 Hr Fire Protective Smoke Curtain with Integral Swing Door or Pass Through Slot
- SD240A® 3 Hr Accordion Curtain for Corner Conditions with Egress